

Wire	2
-------------------	----------

WIRE



WIRE GUIDE FOR PROFILE, STAINLESS STEEL (3695)

SKU:3695

for Uni-profile



WIRE GUIDE, STAINLESS STEEL (3691/ 3692)

SKU:3691/ 3692

for tube Ø19mm

Variations

Type
short (13mm)
long (38mm)



MAXI-WIRE TENSIONER (4998/ 4999)

SKU:4998/ 4999

Variations

Tipo
115mm
120mm



WIRE TENSIONER (4991/ 4992)

SKU:4991/ 4992

Variations

Type
85mm
100mm




WIRE TENSIONER WITH FLAT FRONT EDGE (4981/ 4984)

SKU:4981/ 4984

Variations

Type
1.8-3.0mm / max 400 kg
3.0-4.2mm / max 600kg



COMPACT WIRE TENSIONER (4810)

SKU:4810



ATLAS WIRE, TRANSPARENT (4030/ 4033)

SKU:4030/ 4033



WIRE, STAINLESS STEEL (4056/ 4080/ 4081)

SKU:4056/ 4080/ 4081

Ring ca. 11Kg/ ca. 2.970m (=ca. 270m/ kg)

Roll ca.1000m

Variations

Typ
2mm, Ring of ca. 11Kg/ ca. 2.970m (ca. 270m/kg)
3mm, Ring of ca. 11Kg/ ca. 1320m (=ca. 120m/ kg)

Variations

Type
6x7, 3mm
7x7, 3mm
6x19+1 special, 3mm



WIRE, STAINLESS STEEL
(4020/ 4023/ 4024)

SKU:4020/ 4023/ 4024

without unwinding station

Variations

Type
2mm, Type 1.4301, Ring of ca. 35 kg=1400m
3mm, Type 1.4301 special thickness, ring of ca. 1kg= 17m
4mm, Type 1.4301 special thickness, ca. 1kg= 10m